


- *-DWD

Graphic Specs:





Available Graphics: Dye-Sublimation Graphics Only

Bleeds:

All orbital truss graphics require specific bleeds. The sizes listed above represent the finished graphic size. Please keep all logos, type, and critical information at least 1⁴ in from each edge of the finished graphic.

Dye Sublimation: 2" bleed around the perimeter.

Inkjet & UV: 1/2" bleed around the perimeter.

Color:

All files are printed as CMYK format. All critical Pantone colors need to be called out in the file or specified on the order as Coated or Uncoated swatches.

Resolution:

All raster files (either print files or linked files) must be at 100-120 pixels per inch at 100%.

Finishing Details:

When graphics are notched, a 7/8" square is cut in the appropriate location

FS: Graphics mounted to front of the truss system BS: Graphics mounted to back of the truss system

Dye Sublimation graphics are attached to truss with velcro. Inkjet & UV panels are attached to truss with magnet.

IMPORTANT INFORMATION REGARDING GRAPHIC FILES: Each graphic has a specific code or number located on the graphic.

The electronic print ready files provided must be named accordingly. Using this coding system will allow us to preflight and prepare your files for print more efficiently.

Acceptable File Formats:

Illustrator CS3 or below

Photoshop CS3 or below

Art time will be charged if files

guidelines. When sending files

art (fonts, linked images, etc.)

Font Specifications:

to outlines.

Fonts must be converted


need to be fixed or altered to meet

please be sure to include all support

If you fail to provide your graphic files in this format, additional charges may be necessary to complete your printed materials.
















Color Coded Parts: Atlantis 1 [OR-K-ATL1], 10' x 10' Kit Size






Color Coded Parts: Atlantis 1 [OR-K-ATL1], 10' x 10' Kit Size









H H

11



SCALE REF = 5ft

