

# Quickwall

## QWK

Create a display on the fly with this easy to assemble, affordable 10' backwall solution including three Retractor 2 banner stands and a compact, hard molded OCB case.



## features and benefits:

### Includes three Retractor 2's

- One Retractor 2 comes complete with base, pole, toprail and bag
- Swivel foot base
- Snap graphic toprail
- 90 day hardware warranty against manufacturer defects

### Includes OCB case

- Hard molded, heavy duty banner stand shipping case
- Carry strap included
- Made from 100% recyclable materials
- Variable height
- Protective foam padding
- Made in the USA

## dimensions:

### Hardware

One Retractor 2:  
33" w x 14.5" d x 83.75" h  
838.2mm(w) x 368.3mm(d) x 2127.25mm(h)

Assembled unit:  
97" w x 20" d x 83.75" h approx.  
2463.8mm(w) x 508mm(d) x 2127.25mm(h)

Assembled unit dimension may vary based on angle of stands

### Shipping

Shipping dimensions - ships in one box  
Each box: 40" l x 17" w x 7" h  
1016mm(l) x 431.8mm(w) x 178mm(h)

Approximate shipping weight:  
35lbs/16kg

### Graphic

One Retractor 2:  
31" w x 77.5" h  
plus 1/2" bleed at the top and 6" bleed at the bottom

Refer to related graphic template for more information

## additional information:

Graphic materials:  
13 oz flatmaxx vinyl or oxford fabric

Recommended spacing: 1.5" between graphics, slightly angled outer stands

Stands are supplied with both clamp and adhesive rails, we recommend use of clamp rail with Quickwall system

We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.

## Quickwall Set-Up



Open the OCB and remove the three Retractor 2s

1




Remove pole from pole compartment in the base of each stand

2




Swivel the stabilizing feet all the way out to steady bases

3



Assemble three piece bungee poles

4



Secure poles in the base of each stand

5




Gently lean each unit back and pull the graphic up by the hook

6



Place hook in top of pole to secure graphics

7



Arrange stands so outer units are angled and graphic flows smoothly


8

## Installing a Graphic



Use clamp rail - open graphic rail and insert graphic into slot

1




firmly press down on rail to close and secure graphic

2



Pull attached leader strip all the way out and push pin in side of base to secure - remove paper backing from the tape on the leader strip



3



Attach bottom of the back side of graphic to the tape on leader strip

4

Installing a Graphic Cont'd.



OCB Adjustable Case



## Check out these related products:

---



Retractor 2  
-Used with Quickwall system



Retractor 4  
-Double sided



Retractor 5  
-Velcro graphic applicatoin



Retractor 6  
-Silver or black hardware



Retractor 10  
-Five feet wide